

Butt Hinges



Aluminum Butt Hinges

Part Number	Matl. Thk.	Open Width	Length	Pin Dia.	Pin Retention	Special Features
5A2025 ♦	.051	2.00	2.50	.125	spun ends	—
6A1015 ♦	.064	1.00	1.50	.125	spun ends	—
6A1515 ♦	.064	1.50	1.50	.125	spun ends	—
6A2020 ♦	.064	2.00	2.00	.125	spun ends	—
6A2025 ♦	.064	2.00	2.50	.125	spun ends	—
6A2030 ♦	.064	2.00	3.00	.125	spun ends	—
6A2525 ♦	.064	2.50	2.50	.125	spun ends	—
6A2530 ♦	.064	2.50	3.00	.125	spun ends	—
6A3030 ♦	.064	3.00	3.00	.125	spun ends	—
8A2020 ♦	.081	2.00	2.00	.187	spun ends	—
8A2025 ♦	.081	2.00	2.50	.187	spun ends	—
8A2525 ♦	.081	2.50	2.50	.187	spun ends	—
9A2030 ♦	.091	2.00	3.00	.187	spun ends	—
9A2530 ♦	.091	2.50	3.00	.187	spun ends	—
9A2535 ♦	.091	2.50	3.50	.187	spun ends	—
9A3030 ♦	.091	3.00	3.00	.187	spun ends	—
9A3035 ♦	.091	3.00	3.50	.187	spun ends	—
9A3535	.091	3.50	3.50	.187	spun ends	—
12A2025 ♦*	.125	2.00	2.50	.250	spun ends	—
12A2030 ♦	.125	2.00	3.00	.250	spun ends	—
12A2525 ♦	.125	2.50	2.50	.250	spun ends	—
12A252502 ♦	.125	2.50	2.50	.250	spun ends	(6) Ø.250 holes
12A2530 ♦	.125	2.50	3.00	.250	spun ends	—
12A3030 ♦	.125	3.00	3.00	.250	spun ends	—
12A3040 ♦	.125	3.00	4.00	.250	spun ends	—
12A3540 ♦	.125	3.50	4.00	.250	spun ends	—
12A4040 ♦*	.125	4.00	4.00	.250	spun ends	—

- ▶ mill finish * indicates money saver
▶ no holes unless indicated ♦ indicates stock item

Stainless Steel Butt Hinges

Part Number	Matl. Thk.	Open Width	Length	Pin Dia.	Pin Retention	Special Features
3SS102001 ♦	.030	1.00	2.00	.066	staked	—
6SS1515 ♦	.060	1.50	1.50	.125	staked	—
6SS1520 ♦	.060	1.50	2.00	.125	staked	—
6SS2020 ♦	.060	2.00	2.00	.125	staked	—
6SS2025 ♦	.060	2.00	2.50	.125	staked	—
6SS2030 ♦	.060	2.00	3.00	.125	spun ends	—
6SS2525 ♦	.060	2.50	2.50	.125	spun ends	—
6SS2530 ♦	.060	2.50	3.00	.125	spun ends	—
7SS2021 ♦	.075	2.00	2.00	.187	spun ends	—
7SS2025 ♦	.075	2.00	2.50	.187	spun ends	—
7SS2525 ♦	.075	2.50	2.50	.187	spun ends	—

- ▶ no holes * indicates money saver
▶ 302/304SS leaves and pins ♦ indicates stock item

Part Number	Matl. Thk.	Open Width	Length	Pin Dia.	Pin Retention	Special Features
9SS2030 ♦	.090	2.00	3.00	.187	spun ends	—
9SS2530 ♦	.090	2.50	3.00	.187	spun ends	—
9SS3030 ♦*	.090	3.00	3.00	.187	spun ends	—
9SS303002 ♦	.090	3.00	3.00	.187	spun ends	½ swaged (6) Ø.281 Holes
9SS3035 ♦	.090	3.00	3.50	.187	spun ends	—
9SS3535 ♦*	.090	3.50	3.50	.187	spun ends	—
10SS2025	.105	2.00	2.50	.187	spun ends	—
10SS2525 ♦	.105	2.50	2.50	.187	spun ends	—
12SS2030 ♦	.120	2.00	3.00	.250	spun ends	—
12SS2530 ♦*	.120	2.50	3.00	.250	spun ends	—
12SS3030 ♦*	.120	3.00	3.00	.250	spun ends	—
12SS3040 ♦	.120	3.00	4.00	.250	spun ends	—
12SS3535 *	.118	3.50	3.50	.256	spun ends	—
12SS3540 *	.120	3.50	4.00	.250	spun ends	—
12SS4040 ♦*	.120	4.00	4.00	.276	spun ends	—
12SS40402 ♦	.120	4.00	4.00	.276	spun ends	½ swaged
12SS6040	.120	6.00	4.00	.250	none	—

- ▶ no holes * indicates money saver
▶ 302/304SS leaves and pins ♦ indicates stock item

Type 316SS Butt Hinges

Part Number	Material Thickness	Open Width	Length	Pin Diameter	Pin Retention
6SST1515 ♦	.060	1.50	1.50	.125	staked
6SST1520 ♦	.060	1.50	2.00	.125	staked
6SST2020 ♦	.060	2.00	2.00	.125	staked
6SST2525 ♦	.060	2.50	2.50	.125	staked
7SST2020 ♦	.075	2.00	2.00	.187	spun ends
9SST2030	.090	2.00	3.00	.187	spun ends
9SST3030 ♦	.090	3.00	3.00	.187	spun ends
12SST2030 ♦	.120	2.00	3.00	.250	spun ends
12SST3030 ♦	.120	3.00	3.00	.250	spun ends
12SST3040 ♦	.120	3.00	4.00	.250	spun ends
12SST4040 ♦	.120	4.00	4.00	.250	spun ends
18SST4040 ♦	.180	4.00	4.00	.375	spun ends

- ▶ no holes ♦ indicates stock item