

# MODULAR, COMPOSITE L-HANDLES W/ CONFIGURABLE ASSEMBLIES

Build the right door latching system for  
your HVAC/Enclosure application.

1154 series

NEW  
PRODUCT  
FAMILY



HANDLES	ESCUTCHEONS & SHAFTS	CAMS	CONNECTING RODS	CATCH & INSIDE HANDLES
<p><b>NON-LOCKING OUT-SWING 1154</b></p> <p><b>NON-LOCKING IN-SWING 1154-0XX</b></p> <p><b>PADLOCK OUT-SWING 1154LK</b></p> <p><b>KEY-LOCKING OUT-SWING 1154-333</b></p> <p><b>TOOL ACTIVATED OUT-SWING 1154-T01</b></p> <p><b>PADLOCK IN-SWING 1154LK-0XX</b></p> <p><b>KEY-LOCKING IN-SWING 1154-3330XX</b></p> <p><b>TOOL ACTIVATED IN-SWING 1154LK-T0X0XX</b></p> <p><b>IN-SWING ROLLER CAMS</b></p> <p><b>SHORT STRAIGHT C25S</b></p> <p><b>LONG STRAIGHT C25L</b></p> <p><b>OFFSET STRAIGHT C25-10, C25L-15</b></p>	<p>LENGTHS AVAILABLE FOR 25 / 50 / 75 / 100MM DOOR THICKNESSES</p> <p><b>LOCATING STUD INSTALLATION 1154E-XX</b></p> <p><b>CUT-OUT FOR RH &amp; LH ROTATION</b></p> <p><b>SINGLE HOLE INSTALLATION 1154E-QXX</b></p> <p><b>CUT-OUT FOR SINGLE HOLE</b></p> <p><b>ESCUTCHEON CAP 1154C</b></p>	<p>1. CAMS MATERIAL: ZINC PLATED STEEL 2. ADAPTERS MATERIAL: DIE CAST ZINC 3. ADAPTERS MAY BE REMOVED IN ORDER TO USE THE FLAT END RODS WITH HOLES</p> <p><b>LONG ROLLER CAM 696</b></p> <p><b>SHORT ROLLER CAM 696-01</b></p> <p><b>CAM ROLLER 697-01</b></p> <p><b>CAM ROLLER 698</b></p> <p><b>CAM ROLLER 697</b></p> <p><b>ONE-POINT 50C-X</b></p> <p><b>TWO-POINT 50C00</b></p> <p><b>THREE-POINT WITH NO ADAPTERS 12C4X</b></p> <p><b>LINKAGE C23</b></p> <p><b>THREE-POINT WITH ADAPTERS 12C4X</b></p>	<p><b>8.00MM DIAMETER</b></p> <p>1. MATERIAL: ZINC PLATED STEEL 2. WHEEL MATERIAL: PLASTIC 3. CUSTOM LENGTHS AVAILABLE UPON REQUEST</p> <p><b>PERPENDICULAR FLAT END 744-X</b></p> <p><b>IN-LINE FLAT END 744A-X</b></p> <p><b>ROUND 747-X</b></p> <p><b>ROUND WITH WHEELS 743-X</b></p>	<p><b>SAFETY CATCH C24</b></p> <p><b>IN-LINE HANDLE (90° ANGLE) 364-01, 364BK-01</b></p> <p><b>DIAGONAL HANDLE (45° ANGLE) 364-02, 364BK-02</b></p> <p><b>GUIDES</b></p> <p>1. MATERIAL: PLASTIC WITH STEEL INSERT 2. INSERT HAS M6 THREAD AND ZINC PLATED FINISH</p> <p><b>TALL 702-05</b></p> <p><b>SHORT 702-06</b></p>

## HIGHLIGHTS / FEATURES

- Black glass reinforced nylon assemblies are UV stable and UL94HB flammability rated for optimal durability, thermal protection, and performance.
- Exterior handle configurations are available for Out-swing & In-swing applications; includes non-locking and tool secured or key-locking options.
- Handles are removable to prevent damage during unit transporting, and numerous interior multi-point connecting hardware solutions are available.
- Modular design allows for unassembled shipping and easy service or replacement in the field.
- Industry standard cut out for seamless integration into current designs.
- Mix and match components for use on doors with different thicknesses and latching orientations.
- Suitable for HVAC enclosure doors and other applications requiring gasket compression for a tight seal.

**SIERRA PACIFIC**  
ENGINEERING AND PRODUCTS

Quality & Service Taken Personally®

AS9100  
ISO 9001

www.spep.com

Global Headquarters  
4041 Via Oro Ave.  
Long Beach, CA 90810

Distribution Centers:  
Los Angeles  
Dallas • Chicago

**CONTACT A SPEP SALES REP FOR MORE INFO**

☎ 888.444.6437

✉ info@spep-marketing.com