



Part Number	90° Rotation	Locking	Keyed (2 Keys/Lock)	Shaft Length	Shaft Style	Finish	Mount	Mounting Centers
3362 *	90° CW	yes	CH751					
336201 *	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.813 [46.04]
3363 *	90° CW	no	non-locking					
336301 *	90° CC	no	non-locking					
3462 *	90° CW	yes	CH751					
346201 *	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.813 [46.04]
3463 *	90° CW	no	non-locking					
346301 *	90° CC	no	non-locking					
3360	90° CW	yes	CH751			chrome		
336001BK	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	matte black powder coat	front	2.000 [50.80]
3360BK	90° CW	yes	CH751			matte black powder coat		
336003	360°	no	non-locking					
336004	360°	yes	CH751					
336001	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	2.000 [50.80]
3361	90° CW	no	non-locking					
336101	90° CC	no	non-locking					
3460	90° CW	yes	CH751					
346001	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	2.000 [50.80]
3461	90° CW	no	non-locking					
346101	90° CC	no	non-locking					
3364 *	90° CW	yes	CH751					
336401 *	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	2.250 [57.15]
3365 *	90° CW	no	non-locking					
336501 *	90° CC	no	non-locking					
3464 *	90° CW	yes	CH751					
346401 *	90° CC	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	2.250 [57.15]
3465 *	90° CW	no	non-locking					
346501 *	90° CC	no	non-locking					

- ▶ material: die cast zinc
- ▶ achieve NEMA 12 and IP64 enclosure access requirements when combined with escutcheon gasket sold separately, part no. **336G**
- ▶ meets ADA requirements
- ▶ includes dust shutter
- ▶ locking handles include (2) ringed keys
- ▶ front-mount handles do not include mounting screws (1/4" or #14 recommended)
- ▶ blind-mount handles include (2) 1/4 - 20 x .63 [16.0] long mounting screws
- ▶ all handles include 3/8"-24 keeps nut
- ▶ * non-stock part
- ▶ see accessories starting on pg. 58